

TABLE TYPE STEAM STERILIZERS WITH PULSE-VACUUM SYSTEM



MODEL: C260228001

Use

The table type sterilizers are safely auto-controlled, which are designed for the dental clinics, hospitals, school lab, scientific research institutions and laboratory. And most suitable for sterilizing of surgical, dental and eye instruments, glassware medicine, culture medium and biological dressing, food, etc.

Characteristics

- ◆ Standard Class B with three times vacuum and drying, the remaining

temperature of sterilized instrument is less than 0.2%.

- ◆ LCD display working status, touch keys.

- ◆ The vacuum data can reach -0.8bar, it fits various instrument, including package, unpacked, solid, hollow, multi-apertures and inset pipes. It makes sure the instrument can be sterilized completely.

- ◆ Fully computer controlled LCD display bright show. The interface is modularized panel for easy operation.

- ◆ It is installed with BOWIE&DICK which measures the penetration of water steam.

- ◆ It has vacuum test which can make sure the ability of vacuum testing.

- ◆ Fast and independent steam generator.

- ◆ Built-in mini printer which can record the sterilizing information.

- ◆ Equipped with Safety valve, Safety lock door system, Pressure lock system, Pressure or temperature overload protection, Alarm system.

- ◆ It inactivates the HIV, HBV, BSE, and bacillus efficiently.

- ◆ This product is designed for open water tank, water purification, sewage tank separation, convenient and intuitive.

- ◆ The cycle cannot be started if the door is not sealed. Once the cycle is started and running, the sealed door is locked and cannot be opened to ensure operational safety.

PARAMETER

| | | |
|---|-------------------|-------------------|
| Model | 18L | 23L |
| Chamber Volume: | 18L (φ250×360 mm) | 23L (φ250×470 mm) |
| Max working temperature: | 138℃ | 138℃ |
| Max working pressure: | 0.25mpa | 0.25mpa |
| Adjusted sterilizing temperature range: | 55℃~134℃ | 55℃~134℃ |
| Adjusted timer range: | 0~99mins | 0~99mins |
| Adjusted drying time range: | 0~99mins | 0~99mins |
| Heat average: | ≤±1℃ | ≤±1℃ |
| Power: | 2KW/AC220V/50HZ | 2KW/AC220V/50HZ |
| Dimension: | 480*680*455mm | 480*680*455mm |
| Transport dimension: | 580*790*580mm | 580*790*580mm |
| Gross/Net Weight | 56kg/47kg | 57kg/53kg |