

FLOOR TYPE LOW-SPEED CENTRIFUGE

Features

- Super performance
With microprocessor control of speed, no carbon pollution, and low noise and vibration.
- Easy and simple operate
With large LCD touch panel, can operate by touch or keys.
- The wide range of application
Widely used in the field of Radio-immunology, biochemistry, blood center etc.




12×10ml



148×5/7ml



6×500ml



2×2×96 (Holes)

Technical parameters

Model	CCL-DD5			CCL-DD6		
Max Speed	6000r/min			5000r/min		
Max RCF	5120×g			4390×g		
Rotor No.	Capacity(ml)	Speed(rpm)	RCF (xg)	Capacity(ml)	Speed(rpm)	RCF (xg)
No.1 Angle Rotor	12×10	6000	5120	12×10	5000	4390
No.2 Swing Rotor	148×7	4000	3000	148×7	4000	3000
No.3 Swing Rotor	4×750	4000	3500	4×750	4000	3500
No.4 Swing Rotor	6×500	4000	4390	6×500	4000	4390
No.5 Swing Rotor	4×100	4000	4390	4×100	5000	2810
	32×15/10	4000	2810	32×15/10	4000	2810
	48×7	4000	2810	48×7	4000	2810
	72×5	4000	2810	72×5	4000	2810
No.6 Swing Rotor	6×300	4000	3300	6×300	4000	3300
No.9 Micro-Plates Rotor	2×2×96Holes	4000	2300	2×2×96 Holes	4000	2300
Speed Accuracy	±20r/min					
Timer Range	0-99min					
Motor	Microprocessor Control, AC Frequency Motor					
Noise	≤65dB(A)					
Power Supply	AC220V&110V 50Hz 30A					
Dimension	800×600×820(L×W×H)					
Weight	120kg					