

-25~+30°C

Biomedical Portable Cooler

Model:



Applications

Biomedical portable coolers are specially designed to store and transport blood, serum, plasma, vaccines, reagents, and special medicines for epidemic prevention stations, blood banks, health centers, CDC, animal husbandry bureau, army, and pharmaceutical companies.

Features

- Accurate microprocessor controller especially for biomedical use and resolution of 0.1°C.
- Suggested ambient temperature: +10~32°C.
- Integrated and strong PE body to resist impact and corrosion.
- High-efficiency air cooling system to ensure good temperature uniformity.
- Auto switch cooling and heating system to ensure the inside temperature in all climatic conditions.
- Wide voltage design, able to be used when the voltage is between 220V±10% AC and 12V DC.

Security

- Standard protective basket to prevent the samples from being frozen off by the evaporator.
- Built-in backup battery to power the controller and save temp. data when power failure or system error.
- Visual and audible alarm system.
- Power failure protection: turn-on delay of the cooling system after power failure.
- Controller error protection: The cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors fail.

Humanized design

- Different power ports for AC/DC connection to avoid wrong operation.
- Stack-able, friendly for space-limited place.



Specifications

Model NO.	
Main Specifications	
Temperature Range	-25 ~ +30 °C
Ambient Temperature	10~32°C
Capacity (L/Cu. Ft.)	30 / 1.06
Interior Dimensions (W×D×H) mm	364×253×353
Exterior Dimensions (W×D×H) mm	615×370×472
Weight	22 kgs
Noise	45 dB
Control and Power	
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	AC 220V±10%, 50/60Hz; DC 12V
Power	80 W
Electric Current	DC 6.5 A
Power Consumption (kWh/24h)	1.2
Audible and Visual Alarms	
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Refrigeration	
Refrigeration Type	Forced-air Cooling
Defrost	Manual
Compressor (Brand/pcs)	Chinese Brand / 1
Refrigerant / Weight	R134a / 68g
Cabinet	
Door (pcs)	PE Foamed Solid Door / 1
Interior Cabinet Material	PE
Exterior Cabinet Material	PE
Insulation Material	PURF (δ55mm)
Accessories	
Remote Alarm Port	Optional
Temperature Datalogger	Optional
Shipping	
Package	Carton box
Shipping Weight	26 kgs
Shipping Size (W×D×H)	670×440×540
Shipping Volume	0.16 CBM

* Due to continuous product upgrades, the above specifications are for reference only. For the latest specifications, please contact us.