

2~8°C

Biomedical Refrigerator (Forced-air Cooling System)

Model:



Applications

2~8°C biomedical refrigerators are specially designed to store medicines, vaccines, reagents and bio-medical products.

Features

- Microprocessor control, ensure the inside temperature is within 2~8°C, accuracy is 0.1°C
- Suggested ambient temperature: +10~32°C.
- Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.
- Double toughened glass door with heater, available for high humidity area.
- Wide available voltage range: 220V±10%.

Security

- Safety door lock and controller password to prevent unauthorized access.
- 8h built-in backup battery to power the controller and save temp. data when power failure or system error.
- Visual and audible alarm system.
- Power failure protection: turn-on delay of the cooling system after power failure.
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

- Special designed service-free drainage system, ensure no water in the cabinet.
- 10 adjustable shelves for easy storage.
- Casters with stoppers for easy moving and fixation.
- Auto on/off LED light with manual switch on the control panel.
- Auto on/off cooling fan to prevent cold air from leaking out when the door is opening.

Specifications

Model NO.	
Main Specifications	
Temperature Range	2 ~ 8 °C
Ambient Temperature	10~32°C
Capacity (L/Cu. Ft.)	1000 / 35.31
Interior Dimensions (W×D×H) mm	1129×690×1370
Exterior Dimensions (W×D×H) mm	1229×882×1895
Weight	160 kgs
Noise	53 dB
Control and Power	
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	545 W
Electric Current	3.13 A
Power Consumption (kWh/24h)	10.5
Audible and Visual Alarms	
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 48h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration	
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	Chinese Brand / 1
Refrigerant / Weight	R290 / 100g
Cabinet	
Door (pcs)	Self-closing Heating Glass Door / 2
Adjustable Shelf (pcs)	10
Interior Cabinet Material	Stainless Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (δ50mm)
Door Lock	Yes
LED Lamp	Yes
Test Hole (pcs)	1
Castors / Leveling Feet (pcs)	4 / 2
Accessories	
Remote Alarm Port	Yes
USB Data Download Port	Yes
RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Temperature Chart Recorder	Optional
Shipping	
Package	Carton box with pallet
Shipping Weight	195 kgs
Shipping Size (W×D×H)	1280×920×1980
Shipping Volume	2.33 CBM

* Due to continuous product upgrades, the above specifications are for reference only. For the latest specifications, please contact us.