



## Kjeldahl Digestor

Hanon Kjeldahl Digestor adopts advanced high-temperature infrared radiation heating technology and microprocessor control platform, boasts accurate temperature control and quick temperature rise. It has two kinds of temperature rise modes: linear and curve temperature rise mode, and offers 20 digestion programs for control of temperature rise curves.

Neutralization system has many functions such as triple filtration, condensate recovery of exhaust gas, filtration and neutralization device. The product adopts high-quality anticorrosive pumps, low noise, strong suction, reduce exhaust emissions, eco-friendly.



### Characteristic

- 20 positions enhance working efficiency rapidly.
- Graphite block have longer life after special anti-oxidation processing and heating more uniform.
- Corrosion-resistant design.
- It adopts advanced PID temperature control technology, high accuracy heating up to 400°C only 25 minutes.
- Multi-protection, Over-current protection, high temperature warning, overload protection.
- It adopts 5.7" color screen, easy for use.
- Standard configuration with waste gas collection hood WD03.
- Temperature control model, program control, curve and linear temperature rise.

### Exhausting System

- Module design, compact appearance.
- Absorption device area is transluence design, easy for inspection and changing.
- Suction pressure is adjustable when become negative, to avoid acid gas spilling oremptying.
- Anticorrosion vacuum pump, low noise, large suction, reduce wasted gas exhausting and environmental friendly.
- Ternary filtration system (water condensation, alkali neutralization and active carbon filtration) ensure perfect neutralization and absorption performance. PTFE anticorrosion pipe design, improve using life.





## Kjeldahl Digester

Hanon Kjeldahl Digester has the advantages of fast, efficient and convenient digestion. It is suitable for food, pharmaceutical, agricultural and other industries, as well as universities and scientific research departments to digest soil, feed and other samples before chemical analysis.

Graphite block have longer life after special anti-oxidation processing.

It adopt advanced PID temperature control technology, high accuracy heating up to 400°C only cost 25 minutes.



**Gas Collection Hood**

Using PFA sealed cap, longer life, dealing effect well.

Clip-on sealing cap, easy for changing.

Specialized water jet vacuum pump is adopted, don't need electric power.

Drip tray design, reduce corrosion damage from acid solutions.

### Characteristic

- 20 positions, enhance working efficiency rapidly.
- Corrosion-resistant design.
- It adopt advanced insulation technology, eco-friendly, reduce energy intensity maximum limitedly.
- Multi-protection, Over-current protection, high temperature warning, overload protection.
- LCD display.
- It's used with microwave reaction system, pretreat for microwave digestion or removing acid after digestion.
- Linear and curve temperature rise mode, up to 5 stages temperature setting.
- Curve temperature rise and linear temperature rise two temperature control modes.

The SH220F has two temperature control modes: curve heating and linear temperature heating. It can edit and store 10 groups of digestion programs. Each group can set up a segment temperature and time gradient of up to 5 to meet different experimental needs of users.

Note: "●"with the same technical index; "—"without

### Technical data

Temperature range	Room temperature +5 - 450 C	●
Temperature accuracy	±1 C	●
Heating method	Infrared heating and high-purity graphite conduction	●
Heating insulation method	Unique air duct insulation technology	●
Digestion tube capacity	300mL	●
Capacity per batch	20pcs/batch	●
Power supply	220 VAC±10% 50/60Hz	●
Power	3600W	●
Dimensions	515mm*458mm*730mm	515mm*421mm*211mm
Net weight	40Kg	25Kg