



Auto Lensmeter



Auto Lensmeter

China Care Medical Equipment Co.,Ltd
Address: Room B101, Zhongbang Business Building, PuXing
Road No. 87, Tianhe, Guangzhou,
China web: www.chinacaremedical.com

Features

- ◆ Compact and light
- ◆ Tilting TFT color LCD touch screen (AL-360: 5.6 inch, AL-360A: 7 inch) clear view, easy and convenient operation.
- ◆ Built-in thermal printer, and also can be connected to computer, and display the data on computer.
- ◆ Built-in UV tester
- ◆ PD measuring
- ◆ Automatic recognition of single and progressive lens
- ◆ Memory Function

Specification

Sphere:	0~±25D 0.01/0.12/0.25D steps
Cylinder:	0~±9.99D 0.01/0.12/0.25D steps
Axis:	0°~180° (1°step)
ADD:	0~+9.99D 0.01/0.12/0.25D steps
Prism degree:	0~15 Δ 0.01/0.12/0.25 Δ steps
Cylinder:	+,+/-,-
Prism:	X-Y,P-B
Contact lens:	Soft/hard
Measuring mode:	Single/progressive/ automatic recognition contact lens
Diameter of lens:	Ø 20~108mm
PD:	45~90mm, 0.25mm steps
Speed:	0.1S
ABBE:	30~60
Display:	TFT LCD (5.6") ,LFT LCD (7")
Printer:	Thermal print
Dimensions:	222(D)×161(W)×372(H)mm
Package:	515(H)×320(W)×360(D)mm
Weight:	~5KG
Power supply:	100~120V/200~220V 50/60HZ

Better Detail For Better Quality
Better Detail For Better Quality