



Skype: chinacaremed

Facebook: China care medical

Wechat: joseph20130708

Whatsapp: +86 139 2648 0041

Email: joseph@chinacaremedical.com

Website: www.chinacaremedical.com

Add: Room B205, Changsheng Business Building, Daguan South Road No 26, Tianhe, Guangzhou, China





Skype: chinacaremed

Facebook: China care medical

Wechat: joseph20130708

Whatsapp: +86 139 2648 0041

Email: joseph@chinacaremedical.com

Website: www.chinacaremedical.com

Add: Room B205, Changsheng Business Building, Daguan South Road No 26 ,Tianhe,Guangzhou, China





Skype: chinacaremed

Facebook: China care medical

Wechat: joseph20130708

Whatsapp: +86 139 2648 0041

Email: joseph@chinacaremedical.com

Website: www.chinacaremedical.com

Add: Room B205, Changsheng Business Building, Daguan South Road No 26 ,Tianhe,Guangzhou, China



Features

- 1 Touch operation or continuous mode
- 2 Fixed Speed 2500rpm
- 3 Used for various mixing applications with optional adapters
- 4 Specially designed vacuum suction feet for body stability
- 5 Robust aluminum-cast construction

Specifications

Voltage: 110-120V/220-230V,50/60Hz

Power: 60W



Skype: chinacaremed

Facebook: China care medical

Wechat: joseph20130708

Whatsapp: +86 139 2648 0041

Email: joseph@chinacaremedical.com

Website: www.chinacaremedical.com

Add: Room B205, Changsheng Business Building, Daguan South Road No 26, Tianhe, Guangzhou, China

Mixing motion: Orbital

Orbital diameter: 4mm

Motor type: Shaded pole motor

Motor rating input: 58W

Motor rating output: 10W

Speed range: 0-2500rpm

Speed display: -

Run type: Touch operation/Continuous

Dimension[W×H×D]: 127×130×160mm

Weight: 3.5kg

Permissible ambient temperature: 5-40 degree

Permissible relative humidity: 80%

Protection class: IP21